

Product Specifications	
UPC:	785007555158
Minimum Cable Outer Diameter:	0.47 Inch
Maximum Cable Outer Diameter:	0.87 Inch
Material:	Polyamide 6
Approval:	UL 1682, CSA C22.2
Additional Information:	Applicable Standard IEC 309-1/309-2; Color Red; Overall Dimension 3.94 Inch Dia x 7.2 Inch L; Enclosure IP44; Application Agriculture, Chemical Processing, Construction, Entertainment, Food Processing, Heavy Manufacturing, Light Manufacturing, Waste Water
Catalog Number:	52984
Type:	Polarized
Constructional Feature:	Splash Proof
Voltage Rating:	220/240/380/415 V
Current Rating:	32 Ampere
Number of Poles:	4
Number of Wires:	5
Grounding Style:	Grounding
CATALOG DESCRIPTION:	32 AMP SPLASHPROOF (IP 44 SUITABILITY) CONNECTOR, 4 POLE 5 WIRE, RED
Category:	Pin & Sleeve Devices
Full Size Image	
Full Technical Description:	Polarized Type; Polyamide 6 Material; 0.47 Inch min. Cable Outer Diameter; 0.87 Inch Max. Cable Outer Diameter; 5 Wire(S); UL 1682, CSA C22.2 Approval; 220/240/380/415 V Voltage Rating; 32 Ampere Current Rating; 4 Pole(S); Splash Proof; Grounding Grounding Style; Applicable Standard IEC 309-1/309-2; Color Red; Overall Dimension 3.94 Inch Dia X 7.2 Inch L; Enclosure IP44; Application Agriculture, Chemical Processing, Construction, Entertainment, Food Processing, Heavy Manufacturing, Light Manufacturing, Waste Water Treatment
Manufacturer:	Pass & Seymour Inc. Wiring Devices & Accessories
Manufacturer Brand:	Pass & Seymour Inc. Wiring Devices & Accessories
Product Brochure	
Product Description:	P&S 52984 Connector 400V/32A 3P+N+E Ip44