

Especificaciones



Eaton CHSPT2SURGE

Eaton SPD Type 2 CHSP Service Entrance Surge Protection, 120/240V line, 150V L-N, 300V L-L MCOV, 700V L-N, 1200V L-L, 900V N-G, 700V L-G VPR, 22 kA SCCR, NEMA 4, Single-phase, 60 Hz, 5 kA nominal current discharge, 36 kA surge current

General specifications

PRODUCT NAME	Eaton CHSPT2 surge protection device
CATALOG NUMBER	CHSPT2SURGE
UPC	786685971285
PRODUCT LENGTH/DEPTH	7.5 in
PRODUCT HEIGHT	2 in
PRODUCT WIDTH	5 in
PRODUCT WEIGHT	0.9 lb
CERTIFICATIONS	UL Recognized cUL Certified UL 1449
CATALOG NOTES	5kA nominal discharge current. Has 36kA one time surge current rating.

Especificaciones del producto

FREQUENCY RATING	60 Hz
INTERRUPT RATING	200 kAIC
NOMINAL DISCHARGE CURRENT	5 kA
OPERATING VOLTAGE	150V L-N, 300V L-L
PROTECTION	700V L-N, 1200V L-L, 900V N-G, 700V L-G
VOLTAGE RATING	120/240 V
ENCLOSURE	NEMA 4
PHASE	Single-phase
SURGE CURRENT	36 kA
SHORT-CIRCUIT RATING	22000 kA
OPERATING TEMPERATURE	-40 to 50 °C
TYPE	Surge protection device
SPECIAL FEATURES	Meets or exceeds the requirements specified in IBC ®2006, CBC2007, and UBC®Zone 4

Recursos

GUÍAS DE
ESPECIFICACIONES DE
PRODUCTO

[Eaton Specification Sheet -
CHSPT2SURGE](#)

NOMBRE DE PROYECTO:

NÚMERO DE PROYECTO:

PREPARADO POR:

FECHA:



Eaton Corporation plc Eaton House
Carretera 30 Pembroke
Dublín 4, Irlanda
Eaton.com

© 2025 Eaton. Todos los derechos reservados.

Síguenos en las redes sociales para que conozca la información sobre productos y soporte más reciente.

